



**NOTES:**

1. Material is 3/16" FR-4 Fiberglass sheet.
2. 2 pieces.
3. Holes are in a 16 x 16 grid with horizontal hole spacing of 1.100" and vertical spacing of 1.000".
4. Hole tolerances are +0.015" -0.000" on diameter, +/- 0.025" on nominal hole position.
5. Piece dimensional tolerance is +0.000", -0.030".
6. All holes to be de-burred.

SIZE	REV	DRAWING #
A		TRG036-A-1

DWN BY	Leo Greiner	DATE	7/15/98	SCALE	
COG. ENG.	Leo Greiner	DATE	7/15/98	DO NOT SCALE DRAWING	
ALL SCREW THREADS PER ANSI 14.6 BREAK EDGES 0.020 MAX ON MACHINE WORK. REMOVE BURRS, LOOSE SCALE AND WELD SPLATTER REFERENCE - ANSI 14.5 & B46.1				UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE INCHES DECIMAL TOLERANCES .X = ±0.06 .XX = ±0.02 .XXX = ±0.004 ANGULAR TOLERANCE ± 1 DEG.	

UC Berkeley - Space Sciences Laboratory Crawford Group	
TITLE	
STAR LBL CTB patch panel	